

Liquid Flow Technical Data

LIQUID FLOW RATE - C_v METHOD

The C_v method of rating flow capacity of various devices employs empirical data based on water flow.

The basic formula for water flow is:

$$Q = C_v \sqrt{\Delta P}$$

Q = flow in GPM
 ΔP = pressure differential in psi
 C_v = flow factor

For a flow of 1 gpm at ΔP = 1, the C_v = 1

To obtain the water flow rate through precision orifices use the above equation and obtain the C_v value from the charts on pages 3-4.

Example:

Size No. 100 (.100" dia.) has a C_v = .23

For a 25 psig pressure differential: $Q = C_v \sqrt{\Delta P} = .23 \sqrt{25} = 1.15 \text{ GPM}$

Selected flow data is presented on pages 3-4. The chart data assumes flooded conditions on both sides of the orifice. This is particularly important for orifices less than .020" diameter because of surface tension influences.

FLOW CONVERSIONS

- GPM** – gallons per minute
- LPM** – liters per minute
- CCM** – cubic centimeters per minute
- CFH** – cubic feet per hour
- CFM** – cubic feet per min.

$$\begin{aligned} \text{GPM} \times 3.785 &= \text{LPM} \\ \text{GPM} \times 3785 &= \text{CCM} \\ \text{GPM} \times .1337 &= \text{CFM} \\ \text{GPM} \times 8.021 &= \text{CFH} \\ \text{CCM} \times .001 &= \text{LPM} \end{aligned}$$

Example:

25 GPM x 3.785 = 94.625 LPM

SPECIFIC GRAVITY – OTHER LIQUIDS

For liquids other than water, the equation becomes:

$$Q = C_v \sqrt{\frac{\Delta P}{S.G.}}$$

Where:
 S.G. = Specific gravity of the liquid
 (The specific gravity of water is 1.0)

To obtain the flow rate of an oil with S.G. = .85, use the above equation and obtain the C_v value from the charts on pages 3-4.

Example: Size No. 100 (.100" dia.) has a C_v = .23

For a 25 psig pressure differential: $Q = C_v \sqrt{\frac{\Delta P}{S.G.}} = .23 \sqrt{\frac{25}{.85}} = 1.25 \text{ GPM}$

Specific Gravity of Various Liquids Relative to Water @ 60°F

Alcohol, Ethyl	.79	Diesel Oil	.85
Gasoline	.75	Lube Oil	.90
Glycerine	1.26	Turpentine	.87
Kerosene	.80	Water	1.00

800.533.3285

203.261.8331- Fax

P.O. Box 316 • Monroe, CT 06468

info@okeefecontrols.com

www.okeefecontrols.com

OTHER ORIFICE SIZES (Not on Charts)

Extension of Orifice Flow Data

Using the C_v method for liquid flow, and using measured C_v data we can derive the following formula to calculate required orifice sizes.

$$d_L = \sqrt{\frac{1}{22.5} \frac{Q_L}{\sqrt{\Delta P}}}$$

Where:

d_L = diameter of unknown orifice (in.)
 Q_L = required flow (gpm)

Example: Flow rate required = .5 GPM @ $\Delta P = 1.0$ psi

$$d_L = \sqrt{\frac{1}{22.5} \frac{.5}{\sqrt{1}}} = .149 \text{ in. dia.}$$

Also, to obtain the C_v

$$C_{vL} = \frac{Q_L}{\sqrt{\Delta P}} = \frac{.5}{1} = .5$$

C_{vL} = the C_v for the orifice with diameter = d_L

PRESSURE CONVERSIONS

PSIG - pounds per square inch gage

Kg/CM² - kilograms per square centimeters

KPA - kilo pascals

Bar - unit of pressure equal to 1 atmospheric pressure at sea level

In-H₂O - pressure produced by 1" H₂O

$$\text{PSIG} \times .0703 = \text{Kg/CM}^2$$

$$\text{PSIG} \times 6.895 = \text{KPA}$$

$$\text{PSIG} \times .0689 = \text{Bars}$$

$$\text{PSIG} \times 27.68 = \text{In. H}_2\text{O}$$

Example:

$$25 \text{ psig} \times 6.895 = 172.37 \text{ KPA}$$

Metal Orifice Water Flow – Gallons/Minute



If it's about precision, it's O'Keefe.

Orifice Diameter Inches	0.004	0.005	0.006	0.007	0.008	0.009	0.010	0.011	0.012	0.013	0.014	0.015	0.016	0.017	0.018	0.019	0.020	0.021	0.022	0.023	0.024	0.025	0.026	0.027	0.028	0.029	0.031	0.032	0.033
Size Number	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	31	32	33
C _v	0.00035	0.0006	0.0009	0.0012	0.0015	0.0019	0.0025	0.0028	0.0034	0.0038	0.0043	0.0050	0.0055	0.0067	0.0073	0.0080	0.009	0.010	0.011	0.012	0.013	0.014	0.016	0.017	0.018	0.019	0.022	0.024	0.025
1	0.00035	0.0006	0.0009	0.0012	0.0015	0.0019	0.0025	0.0028	0.0034	0.0038	0.0043	0.0050	0.0055	0.0067	0.0073	0.0080	0.009	0.010	0.011	0.012	0.013	0.014	0.016	0.017	0.018	0.019	0.022	0.024	0.025
2	0.00049	0.0009	0.0012	0.0017	0.0021	0.0027	0.0035	0.0040	0.0048	0.0054	0.0061	0.0071	0.0078	0.0095	0.0103	0.0113	0.012	0.014	0.016	0.017	0.018	0.020	0.023	0.024	0.025	0.027	0.031	0.034	0.035
3	0.00061	0.0011	0.0015	0.0021	0.0026	0.0033	0.0043	0.0048	0.0059	0.0066	0.0074	0.0087	0.0095	0.0116	0.0126	0.0139	0.015	0.017	0.019	0.021	0.023	0.024	0.028	0.029	0.031	0.033	0.038	0.042	0.043
4	0.00070	0.0012	0.0017	0.0024	0.0030	0.0038	0.0050	0.0056	0.0068	0.0076	0.0086	0.0100	0.0110	0.0134	0.0146	0.0160	0.018	0.019	0.022	0.024	0.026	0.028	0.032	0.034	0.036	0.038	0.044	0.048	0.050
5	0.00078	0.0014	0.0019	0.0027	0.0034	0.0042	0.0056	0.0063	0.0076	0.0085	0.0096	0.0112	0.0123	0.0150	0.0163	0.0179	0.020	0.021	0.025	0.027	0.029	0.031	0.036	0.038	0.040	0.042	0.049	0.054	0.056
6	0.00086	0.0015	0.0021	0.0029	0.0037	0.0047	0.0061	0.0069	0.0083	0.0093	0.0105	0.0122	0.0135	0.0164	0.0179	0.0196	0.022	0.024	0.027	0.029	0.032	0.034	0.039	0.042	0.044	0.047	0.054	0.059	0.061
7	0.00093	0.0016	0.0023	0.0032	0.0040	0.0050	0.0066	0.0074	0.0090	0.0101	0.0114	0.0132	0.0146	0.0177	0.0193	0.0212	0.023	0.025	0.029	0.032	0.034	0.037	0.042	0.045	0.048	0.050	0.058	0.063	0.066
8	0.00099	0.0017	0.0024	0.0034	0.0042	0.0054	0.0071	0.0079	0.0096	0.0107	0.0122	0.0141	0.0156	0.0190	0.0206	0.0226	0.025	0.027	0.031	0.034	0.037	0.040	0.045	0.048	0.051	0.054	0.062	0.068	0.071
9	0.00105	0.0018	0.0026	0.0036	0.0045	0.0057	0.0075	0.0084	0.0102	0.0114	0.0129	0.0150	0.0165	0.0201	0.0219	0.0240	0.026	0.029	0.033	0.036	0.039	0.042	0.048	0.051	0.054	0.057	0.066	0.072	0.075
10	0.00111	0.0019	0.0027	0.0038	0.0047	0.0060	0.0079	0.0089	0.0108	0.0120	0.0136	0.0158	0.0174	0.0212	0.0231	0.0253	0.028	0.030	0.035	0.038	0.041	0.044	0.051	0.054	0.057	0.060	0.070	0.076	0.079
15	0.00136	0.0024	0.0033	0.0046	0.0058	0.0074	0.0097	0.0108	0.0132	0.0147	0.0167	0.0194	0.0213	0.0259	0.0283	0.0310	0.034	0.037	0.043	0.046	0.050	0.054	0.062	0.066	0.070	0.074	0.085	0.093	0.097
20	0.00157	0.0027	0.0038	0.0054	0.0067	0.0085	0.0112	0.0125	0.0152	0.0170	0.0192	0.0224	0.0246	0.0300	0.0326	0.0358	0.039	0.043	0.049	0.054	0.058	0.063	0.072	0.076	0.080	0.085	0.098	0.107	0.112
30	0.00192	0.0033	0.0047	0.0066	0.0082	0.0104	0.0137	0.0153	0.0186	0.0208	0.0236	0.0274	0.0301	0.0367	0.0400	0.0438	0.048	0.053	0.060	0.066	0.071	0.077	0.088	0.093	0.099	0.104	0.120	0.131	0.137
40	0.00221	0.0039	0.0054	0.0076	0.0095	0.0120	0.0158	0.0177	0.0215	0.0240	0.0272	0.0316	0.0348	0.0424	0.0462	0.0506	0.056	0.061	0.070	0.076	0.082	0.089	0.101	0.108	0.114	0.120	0.139	0.152	0.158
50	0.00247	0.0043	0.0061	0.0085	0.0106	0.0134	0.0177	0.0198	0.0240	0.0269	0.0304	0.0354	0.0389	0.0474	0.0516	0.0566	0.062	0.068	0.078	0.085	0.092	0.099	0.113	0.120	0.127	0.134	0.156	0.170	0.177
60	0.00271	0.0047	0.0067	0.0093	0.0116	0.0147	0.0194	0.0217	0.0263	0.0294	0.0333	0.0387	0.0426	0.0519	0.0565	0.0620	0.068	0.074	0.085	0.093	0.101	0.108	0.124	0.132	0.139	0.147	0.170	0.186	0.194
70	0.00293	0.0051	0.0072	0.0100	0.0125	0.0159	0.0209	0.0234	0.0284	0.0318	0.0360	0.0418	0.0460	0.0561	0.0611	0.0669	0.074	0.080	0.092	0.100	0.109	0.117	0.134	0.142	0.151	0.159	0.184	0.201	0.209
80	0.00313	0.0055	0.0077	0.0107	0.0134	0.0170	0.0224	0.0250	0.0304	0.0340	0.0385	0.0447	0.0492	0.0599	0.0653	0.0716	0.079	0.086	0.098	0.107	0.116	0.125	0.143	0.152	0.161	0.170	0.197	0.215	0.224
90	0.00332	0.0058	0.0082	0.0114	0.0142	0.0180	0.0237	0.0266	0.0323	0.0360	0.0408	0.0474	0.0522	0.0636	0.0693	0.0759	0.083	0.091	0.104	0.114	0.123	0.133	0.152	0.161	0.171	0.180	0.209	0.228	0.237
100	0.00350	0.0061	0.0086	0.0120	0.0150	0.0190	0.0250	0.0280	0.0340	0.0380	0.0430	0.0500	0.0550	0.0670	0.0730	0.0800	0.088	0.096	0.110	0.120	0.130	0.140	0.160	0.170	0.180	0.190	0.220	0.240	0.250

Orifice Diameter Inches	0.035	0.037	0.038	0.039	0.04	0.041	0.042	0.043	0.047	0.052	0.055	0.06	0.063	0.067	0.07	0.073	0.076	0.079	0.081	0.086	0.089	0.094	0.096	0.1	0.104	0.109	0.113	0.12	0.125
Size Number	35	37	38	39	40	41	42	43	47	52	55	60	63	67	70	73	76	79	81	86	89	94	96	100	104	109	113	120	125
C _v	0.028	0.031	0.032	0.033	0.036	0.038	0.039	0.041	0.048	0.059	0.068	0.081	0.088	0.100	0.110	0.120	0.130	0.140	0.150	0.170	0.180	0.200	0.210	0.230	0.250	0.270	0.310	0.340	0.370
1	0.028	0.031	0.032	0.033	0.036	0.038	0.039	0.041	0.048	0.059	0.068	0.081	0.088	0.100	0.110	0.120	0.130	0.140	0.150	0.170	0.180	0.200	0.210	0.230	0.250	0.270	0.310	0.340	0.370
2	0.040	0.044	0.045	0.047	0.051	0.054	0.055	0.058	0.068	0.083	0.096	0.115	0.124	0.141	0.156	0.170	0.184	0.198	0.212	0.240	0.255	0.283	0.297	0.325	0.354	0.382	0.438	0.481	0.523
3	0.048	0.054	0.055	0.057	0.062	0.066	0.068	0.071	0.083	0.102	0.118	0.140	0.152	0.173	0.191	0.208	0.225	0.242	0.260	0.294	0.312	0.346	0.364	0.398	0.433	0.468	0.537	0.589	0.641
4	0.056	0.062	0.064	0.066	0.072	0.076	0.078	0.082	0.096	0.118	0.136	0.162	0.176	0.200	0.220	0.240	0.260	0.280	0.300	0.340	0.360	0.400	0.420	0.460	0.500	0.540	0.620	0.680	0.740
5	0.063	0.069	0.072	0.074	0.080	0.085	0.087	0.092	0.107	0.132	0.152	0.181	0.197	0.224	0.246	0.268	0.291	0.313	0.335	0.380	0.402	0.447	0.470	0.514	0.559	0.604	0.693	0.760	0.827
6	0.069	0.076	0.078	0.081	0.088	0.093	0.096	0.100	0.118	0.145	0.167	0.198	0.216	0.245	0.269	0.294	0.318	0.343	0.367	0.416	0.441	0.490	0.514	0.563	0.612	0.661	0.759	0.833	0.906
7	0.074	0.082	0.085	0.087	0.095	0.101	0.103	0.108	0.127	0.156	0.180	0.214	0.233	0.265	0.291	0.317	0.344	0.370	0.397	0.450	0.476	0.529	0.556	0.609	0.661	0.714	0.820	0.900	0.979
8	0.079	0.088	0.091	0.093	0.102	0.107	0.110	0.116	0.136	0.167	0.192	0.229	0.249	0.283	0.311	0.339	0.368	0.396	0.424	0.481	0.509	0.566	0.594	0.651	0.707	0.764	0.877	0.962	1.047
9	0.084	0.093	0.096	0.099	0.108	0.114	0.117	0.123	0.144	0.177	0.204	0.243	0.264	0.300	0.330	0.360	0.390	0.420	0.450	0.510	0.540	0.600	0.630	0.690	0.750	0.810	0.930	1.020	1.110
10	0.089	0.098	0.101	0.104	0.114	0.120	0.123	0.130	0.152	0.187	0.215	0.256	0.278	0.316	0.348	0.379	0.411	0.443	0.474	0.538	0.569	0.632	0.664	0.727	0.791	0.854	0.980	1.075	1.170
15	0.108	0.120	0.124	0.128	0.139	0.147	0.151	0.159	0.186	0.229	0.263	0.314	0.341	0.387	0.426	0.465	0.503	0.542	0.581	0.658	0.697	0.775	0.813	0.891	0.968	1.046	1.201	1.317	1.433
20	0.125	0.139	0.143	0.148	0.161	0.170	0.174	0.183	0.215	0.264	0.304	0.362	0.394	0.447	0.492	0.537	0.581	0.626	0.671	0.760	0.805	0.894	0.939	1.029	1.118	1.207	1.386	1.521	1.655
30	0.153	0.170	0.175	0.181	0.197	0.208	0.214	0.225	0.263	0.323	0.372	0.444	0.482	0.548	0.602	0.657	0.712	0.767	0.822	0.931	0.986	1.095	1.150	1.260	1.369	1.479	1.698	1.862	2.027
40	0.177	0.196	0.202	0.209	0.228	0.240	0.247	0.259	0.304	0.373	0.430	0.512	0.557	0.632	0.696	0.759	0.82												

Metal Orifice Water Flow – Liters/Minute



If it's about precision, it's O'Keefe.

Orifice Diameter Inches	Supply Pressure – psig																																			
	0.005	0.006	0.007	0.008	0.009	0.010	0.011	0.012	0.013	0.014	0.015	0.016	0.017	0.018	0.019	0.02	0.021	0.022	0.023	0.024	0.025	0.026	0.027	0.028	0.029	0.031	0.032	0.033								
Size Number	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	31	32	33							
C _v	0.00035	0.0006	0.0009	0.0012	0.0015	0.0019	0.0025	0.0028	0.0034	0.0038	0.0043	0.0050	0.0055	0.0067	0.0073	0.0080	0.009	0.010	0.011	0.012	0.013	0.014	0.016	0.017	0.018	0.019	0.022	0.024	0.025	0.026	0.027	0.028	0.029	0.031	0.032	0.033
1	0.0013	0.0023	0.0033	0.0045	0.0057	0.0072	0.0095	0.0106	0.0129	0.0144	0.0163	0.0189	0.0208	0.0254	0.0276	0.0303	0.033	0.036	0.042	0.045	0.049	0.053	0.061	0.064	0.068	0.072	0.083	0.091	0.095							
2	0.0019	0.0033	0.0046	0.0064	0.0080	0.0102	0.0134	0.0150	0.0182	0.0203	0.0230	0.0268	0.0294	0.0359	0.0391	0.0428	0.047	0.051	0.059	0.064	0.070	0.075	0.086	0.091	0.096	0.102	0.118	0.128	0.134							
3	0.0023	0.0040	0.0056	0.0079	0.0098	0.0125	0.0164	0.0184	0.0223	0.0249	0.0282	0.0328	0.0361	0.0439	0.0479	0.0525	0.058	0.063	0.072	0.079	0.085	0.092	0.105	0.111	0.118	0.125	0.144	0.157	0.164							
4	0.0026	0.0046	0.0065	0.0091	0.0114	0.0144	0.0189	0.0212	0.0257	0.0288	0.0326	0.0379	0.0416	0.0507	0.0553	0.0606	0.067	0.073	0.083	0.091	0.098	0.106	0.121	0.129	0.136	0.144	0.167	0.182	0.189							
5	0.0030	0.0052	0.0073	0.0102	0.0127	0.0161	0.0212	0.0237	0.0288	0.0322	0.0364	0.0423	0.0466	0.0567	0.0618	0.0677	0.074	0.081	0.093	0.102	0.110	0.119	0.135	0.144	0.152	0.161	0.186	0.203	0.212							
6	0.0032	0.0057	0.0080	0.0111	0.0139	0.0176	0.0232	0.0260	0.0315	0.0352	0.0399	0.0464	0.0510	0.0621	0.0677	0.0742	0.082	0.089	0.102	0.111	0.121	0.130	0.148	0.158	0.167	0.176	0.204	0.223	0.232							
7	0.0035	0.0061	0.0086	0.0120	0.0150	0.0190	0.0250	0.0280	0.0341	0.0381	0.0431	0.0501	0.0551	0.0671	0.0731	0.0801	0.088	0.096	0.110	0.120	0.130	0.140	0.160	0.170	0.180	0.190	0.220	0.240	0.250							
8	0.0037	0.0065	0.0092	0.0128	0.0161	0.0203	0.0268	0.0300	0.0364	0.0407	0.0460	0.0535	0.0589	0.0717	0.0782	0.0857	0.094	0.103	0.118	0.128	0.139	0.150	0.171	0.182	0.193	0.203	0.236	0.257	0.268							
9	0.0040	0.0069	0.0098	0.0136	0.0170	0.0216	0.0284	0.0318	0.0386	0.0432	0.0488	0.0568	0.0625	0.0761	0.0829	0.0908	0.100	0.109	0.125	0.136	0.148	0.159	0.182	0.193	0.204	0.216	0.250	0.273	0.284							
10	0.0042	0.0073	0.0103	0.0144	0.0180	0.0227	0.0299	0.0335	0.0407	0.0455	0.0515	0.0599	0.0658	0.0802	0.0874	0.0958	0.105	0.115	0.132	0.144	0.156	0.168	0.192	0.203	0.215	0.227	0.263	0.287	0.299							
15	0.0051	0.0089	0.0126	0.0176	0.0220	0.0279	0.0367	0.0411	0.0498	0.0557	0.0630	0.0733	0.0806	0.0982	0.1070	0.1173	0.129	0.141	0.161	0.176	0.191	0.205	0.235	0.249	0.264	0.279	0.323	0.352	0.367							
20	0.0059	0.0103	0.0146	0.0203	0.0254	0.0322	0.0423	0.0474	0.0576	0.0643	0.0728	0.0846	0.0931	0.1134	0.1236	0.1354	0.149	0.163	0.186	0.203	0.220	0.237	0.271	0.288	0.305	0.322	0.372	0.406	0.423							
30	0.0073	0.0126	0.0178	0.0249	0.0311	0.0394	0.0518	0.0581	0.0705	0.0788	0.0892	0.1037	0.1140	0.1389	0.1514	0.1659	0.182	0.199	0.228	0.249	0.270	0.290	0.332	0.352	0.373	0.394	0.456	0.498	0.518							
40	0.0084	0.0146	0.0206	0.0287	0.0359	0.0455	0.0599	0.0670	0.0814	0.0910	0.1029	0.1197	0.1317	0.1604	0.1748	0.1915	0.211	0.230	0.263	0.287	0.311	0.335	0.383	0.407	0.431	0.455	0.527	0.575	0.599							
50	0.0094	0.0163	0.0230	0.0321	0.0402	0.0509	0.0669	0.0749	0.0910	0.1017	0.1151	0.1338	0.1472	0.1793	0.1954	0.2141	0.236	0.257	0.294	0.321	0.348	0.375	0.428	0.455	0.482	0.509	0.589	0.642	0.669							
60	0.0103	0.0179	0.0252	0.0352	0.0440	0.0557	0.0733	0.0821	0.0997	0.1114	0.1261	0.1466	0.1613	0.1965	0.2140	0.2346	0.258	0.281	0.323	0.352	0.381	0.411	0.469	0.498	0.528	0.557	0.645	0.704	0.733							
70	0.0111	0.0193	0.0272	0.0380	0.0475	0.0602	0.0792	0.0887	0.1077	0.1203	0.1362	0.1584	0.1742	0.2122	0.2312	0.2534	0.279	0.304	0.348	0.380	0.412	0.443	0.507	0.538	0.570	0.602	0.697	0.760	0.792							
80	0.0119	0.0207	0.0291	0.0406	0.0508	0.0643	0.0846	0.0948	0.1151	0.1287	0.1456	0.1693	0.1862	0.2268	0.2472	0.2709	0.298	0.325	0.372	0.406	0.440	0.474	0.542	0.576	0.609	0.643	0.745	0.813	0.846							
90	0.0126	0.0219	0.0309	0.0431	0.0539	0.0682	0.0898	0.1006	0.1221	0.1365	0.1544	0.1796	0.1975	0.2406	0.2622	0.2873	0.316	0.345	0.395	0.431	0.467	0.503	0.575	0.610	0.646	0.682	0.790	0.862	0.898							
100	0.0132	0.0231	0.0326	0.0454	0.0568	0.0719	0.0946	0.1060	0.1287	0.1438	0.1628	0.1893	0.2082	0.2536	0.2763	0.3028	0.333	0.363	0.416	0.454	0.492	0.530	0.606	0.644	0.681	0.719	0.833	0.908	0.946							

Orifice Diameter Inches	Supply Pressure – psig																												
	0.035	0.037	0.038	0.039	0.04	0.041	0.042	0.043	0.047	0.052	0.055	0.06	0.063	0.067	0.07	0.073	0.076	0.079	0.081	0.086	0.089	0.094	0.096	0.1	0.104	0.109	0.113	0.12	0.125
Size Number	35	37	38	39	40	41	42	43	47	52	55	60	63	67	70	73	76	79	81	86	89	94	96	100	104	109	113	120	125
C _v	0.028	0.031	0.032	0.033	0.036	0.038	0.039	0.041	0.048	0.059	0.068	0.081	0.088	0.100	0.110	0.120	0.130	0.140	0.150	0.170	0.180	0.200	0.210	0.230	0.250	0.270	0.310	0.340	0.370
1	0.106	0.117	0.121	0.125	0.136	0.144	0.148	0.155	0.182	0.223	0.257	0.307	0.333	0.379	0.416	0.454	0.492	0.530	0.568	0.644	0.681	0.757	0.795	0.871	0.946	1.022	1.173	1.287	1.401
2	0.150	0.166	0.171	0.177	0.193	0.203	0.209	0.219	0.257	0.316	0.364	0.434	0.471	0.535	0.589	0.642	0.696	0.749	0.803	0.910	0.964	1.071	1.124	1.231	1.338	1.445	1.660	1.820	1.981
3	0.184	0.203	0.210	0.216	0.236	0.249	0.256	0.269	0.315	0.387	0.446	0.531	0.577	0.656	0.721	0.787	0.852	0.918	0.983	1.115	1.180	1.311	1.377	1.508	1.639	1.770	2.033	2.229	2.426
4	0.212	0.235	0.242	0.250	0.273	0.288	0.295	0.310	0.363	0.447	0.515	0.613	0.666	0.757	0.833	0.908	0.984	1.060	1.136	1.287	1.363	1.514	1.590	1.741	1.893	2.044	2.347	2.574	2.801
5	0.237	0.262	0.271	0.279	0.305	0.322	0.330	0.347	0.406	0.499	0.576	0.686	0.745	0.846	0.931	1.016	1.100	1.185	1.270	1.439	1.524	1.693	1.778	1.947	2.116	2.285	2.624	2.878	3.132
6	0.260	0.287	0.297	0.306	0.334	0.352	0.362	0.380	0.445	0.547	0.631	0.751	0.816	0.927	1.020	1.113	1.205	1.298	1.391	1.576	1.669	1.854	1.947	2.133	2.318	2.504	2.874	3.153	3.431
7	0.280	0.310	0.320	0.331	0.361	0.381	0.391	0.411	0.481	0.591	0.681	0.811	0.881	1.002	1.102	1.202	1.302	1.402	1.502	1.703	1.803	2.003	2.103	2.304	2.504	2.704	3.105	3.405	3.706
8	0.300	0.332	0.343	0.353	0.385	0.407	0.418	0.439	0.514	0.632	0.728	0.867	0.942	1.071	1.178	1.285	1.392	1.499	1.606	1.820	1.927	2.141	2.248	2.463	2.677	2.891	3.319	3.640	3.961
9	0.318	0.352	0.363	0.375	0.409	0.432	0.443	0.466	0.545	0.670	0.772	0.920	0.999	1.136	1.249	1.363	1.476	1.590	1.703	1.931	2.044	2.271	2.385	2.612	2.839	3.066	3.520	3.861	4.202
10	0.335	0.371	0.383	0.395	0.431	0.455	0.467	0.491	0.575	0.706	0.814	0.970	1.053	1.197	1.317	1.436	1.556	1.676	1.796	2.035	2.155	2.394	2.514	2.753	2.993	3.232	3.711	4.070	4.429
15	0.411	0.454	0.469	0.484	0.528	0.557	0.572	0.601	0.704	0.865	0.997	1.188	1.290	1.466	1.613	1.759	1.906	2.053	2.199	2.492	2.639	2.932	3.079	3.372	3.665	3.958	4.545	4.985	5.424
20	0.474	0.525	0.542	0.559	0.609	0.643	0.660	0.694	0.813	0.999	1.151	1.371	1.490	1.693	1.862	2.031	2.201	2.370	2.539	2.878	3.047	3.386	3.555	3.894	4.232	4.571	5.248	5.756	6.264
30	0.581	0.643	0.663	0.684	0.746	0.788	0.809	0.850	0.995	1.223	1.410	1.679	1.825	2.073	2.281	2.488	2.695	2.903	3.110	3.525	3.732	4.147	4.354	4.769	5.183				